



DEAS 1245: 2024

ICS :55.020

DRAFT EAST AFRICAN STANDARD

Packaging and Transport of Fresh Fruit and Vegetable — Code of practice

EAST AFRICAN COMMUNITY

Copyright notice

This EAC document is copyright-protected by EAC. While the reproduction of this document by participants in the EAC standards development process is permitted without prior permission from EAC, neither this document nor any extract from it may be reproduced, stored or transmitted in any form for any other purpose without prior written permission from EAC.

Requests for permission to reproduce this document for the purpose of selling it should be addressed as shown below or to EAC's member body in the country of the requester:

© East African Community 2023 — All rights reserved

East African Community

P.O. Box 1096,

Arusha

Tanzania

Tel: + 255 27 2162100

Fax: + 255 27 2162190

E-mail: eac@eachq.org

Web: www.eac-quality.net

Reproduction for sales purposes may be subject to royalty payments or a licensing agreement. Violators may be prosecuted.

DEAS FOR PUBLIC REVIEW COMMENTS ONLY

Contents

Page

Foreword	iv
1 Scope	Error! Bookmark not defined.
2 Normative references	Error! Bookmark not defined.
3 Terms and definitions	1
4 General requirements	Error! Bookmark not defined.
5 Information on commercial activities	Error! Bookmark not defined.
6 Bookings and registration	Error! Bookmark not defined.
7 Reception area	Error! Bookmark not defined.
8 Utilities and facilities	Error! Bookmark not defined.
9 Restrooms	Error! Bookmark not defined.
10 Paths and trails	Error! Bookmark not defined.
11 Water-based recreational activities	Error! Bookmark not defined.
11.1 Safety	Error! Bookmark not defined.
11.2 Swimming	Error! Bookmark not defined.
12 Equipment	Error! Bookmark not defined.
13 Signage	Error! Bookmark not defined.
14 Fires	Error! Bookmark not defined.
15 Noise pollution	Error! Bookmark not defined.
16 Maintenance plan	Error! Bookmark not defined.
17 Safety and security	Error! Bookmark not defined.
18 Emergency plan	Error! Bookmark not defined.
19 Staff requirements	Error! Bookmark not defined.
20 Responsible marketing	Error! Bookmark not defined.
21 Customer service	Error! Bookmark not defined.
21.1 Visitor feedback	Error! Bookmark not defined.
21.2 Visitor complaints management system	Error! Bookmark not defined.
Annex A (informative) Environmental considerations	Error! Bookmark not defined.
A.1 Waste minimization, reuse and recycling	Error! Bookmark not defined.
A.2 Energy conservation and management	Error! Bookmark not defined.
A.3 Management of water resources	Error! Bookmark not defined.
A.4 Land use, planning and management	Error! Bookmark not defined.
A.5 Noise	Error! Bookmark not defined.
Bibliography	Error! Bookmark not defined.

Foreword

Development of the East African Standards has been necessitated by the need for harmonizing requirements governing quality of products and services in the East African Community. It is envisaged that through harmonized standardization, trade barriers that are encountered when goods and services are exchanged within the Community will be removed.

The Community has established an East African Standards Committee (EASC) mandated to develop and issue East African Standards (EAS). The Committee is composed of representatives of the National Standards Bodies in Partner States, together with the representatives from the public and private sector organizations in the community.

East African Standards are developed through Technical Committees that are representative of key stakeholders including government, academia, consumer groups, private sector and other interested parties. Draft East African Standards are circulated to stakeholders through the National Standards Bodies in the Partner States. The comments received are discussed and incorporated before finalization of standards, in accordance with the Principles and procedures for development of East African Standards.

East African Standards are subject to review, to keep pace with technological advances. Users of the East African Standards are therefore expected to ensure that they always have the latest versions of the standards they are implementing.

The committee responsible for this document is Technical Committee EASC/TC 009, *Food packaging and labelling*.

Attention is drawn to the possibility that some of the elements of this document shall be subject of patent rights. EAC shall not be held responsible for identifying any or all such patent rights.

Packaging and transport of Fresh fruits and Vegetables — Code of practice

1 Scope

This Draft East African Standard provides guidelines and recommendations for proper packaging and transport of fresh fruit and vegetables in order to maintain produce quality during transportation and marketing.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

There are no normative references in this document.

Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4. Design, condition and loading method of transport equipment

4.1. Mode of transportation and type of equipment should consider:

- destination ;
- value of the produce ;
- degree of produce perishability;
- amount of produce to be transported;
- recommended storage temperature and relative humidity;
- outside temperature conditions at origin and destination points;
- time in transit to reach destination by air, land, or ocean transport;
- freight rates negotiated with the carriers;
- quality of transportation service.

4.2 Reliability and quality of transportation service provided by different carriers must be carefully considered along with the rates charged.

Find the relevant and most current information on available services through contacting shipment agencies at their origin and destination locations

4.3 When available refrigerated trailers and van containers are recommended for most high volume produce with transit and storage lives of a week or more.

After transit, there must be enough remaining produce life for marketing. Carriers utilizing trailers and containers can offer a door-to-door service. This reduces handling, exposure, damage, and theft of the produce.

4.4 Air cargo containers also can be used to provide a door-to-door service.

Produce transported by air is generally high-value and highly perishable. Freight costs are higher by air. Transit times, however, are in terms of hours instead of days.

4.5 Many produce is shipped in unrefrigerated air containers or on air cargo pallets.

This requires close coordination at the origin and destination airports to protect the produce when flights are delayed. Temperature-controlled storage facilities at airports are needed to ensure produce quality. Refrigerated air containers are available and should be used when possible. Use of insulated thermal blankets is an option.

4.6 Produce which can be shipped in refrigerated trailers and van containers are sometimes shipped by air to take advantage of brief market opportunities, such as the beginning of a season when prices are high and supply is limited. A robust and accurate system for monitoring or displaying temperature and relative humidity during transport in integral containers should be considered.

4.7 Long distance transportation through tropical and frigid climates should be rugged well-designed equipment to withstand the transit environment and protect the produce.

Desirable features in refrigerated trailers up to 14.6 m (48 ft) long and van containers up to 12 m (40 ft) long include for example:

- 42000 kJ/h (40000 BTU/h) refrigeration capacity at 38°C (100°F) ambient, 2°C (36°F) return air temperature;
- a continuously operating high capacity evaporator blower for more even produce temperatures and higher relative humidities;
- a solid return air bulkhead at the front of the trailer to ensure air circulation throughout the load;
- vertical ribs on the rear door to assist in air circulation;
- adequate insulation and provisions for heating, when used in regions where weather conditions so demand due to the nature of the produce;
- deep floor grooves or channels, from 50 to 75 mm (2 to 3 mm) in depth to provide an adequate cross-sectional area for air circulation under loads placed directly on the floor;
- supply-air temperature sensing of the operation of the refrigeration unit to reduce produce chilling and freezing injury;
- provisions for ventilation to prevent ethylene or carbon dioxide build up;

- air-ride suspension to reduce the amount of shock and vibration transferred to the shipping containers and the produce inside;
- modern containers in which cold air leaves the front part of the container, but the air flow circulates from below (close to the floor) toward the back, then rising to the upper part of the container.

4.8 Most carriers check their transport equipment before presenting it to the shipper for loading.

The condition of the equipment is critical to maintaining the quality of the produce. Therefore, the shipper also should check the equipment to ensure it is in good working order and meets the needs of the produce. Carriers provide guidance on checking and operating the refrigeration systems.

4.9 All transportation equipment should be checked for:

- **cleanliness** - the load compartment should be regularly cleaned for example by steam cleaning;
- **damage** to walls, floors, doors, ceilings should be in good condition;
- **temperature control** - refrigerated units should be recently calibrated and supply continuous air circulation for uniform produce temperatures.

4.10. Shippers should insist on clean equipment. A load of produce can be ruined by:

- smell from previous deliveries or incompatible loads;
- toxic chemical residues;
- insects nesting in the equipment;
- decaying remains of agricultural produce;
- debris blocking drain openings or air circulation channels along the floor.

4.11 Shippers should insist on well maintained equipment and check for the following:

- damage to walls, ceilings, or floors which can let in the outside heat, cold, moisture, dirt, and insects;
- operation and condition of doors, ventilation openings, and seals;
- provisions for load locking and bracing.

4.12 For refrigerated trailers and van containers, the following additional checks are important :

- ensure there is no leakage,
- proper working of the refrigeration unit
- determine the location of the sensing element which controls the discharge air temperature. If it measures return air temperature, the thermostat may have to be set- higher to avoid chilling injury or freezing injury of the produce
- with the doors closed, have someone inside the cargo area check for light--door gaskets must seal. A smoke generator also can be used to detect leaks;
- the refrigeration unit should cycle from high to low speed when the desired temperature is reached and then back to high speed;

- determine the location of the sensing element which controls the discharge air temperature. If it measures return air temperature, the thermostat may have to be set- higher to avoid chilling injury or freezing injury of the produce;
- a solid return air bulkhead should be installed at the front of the trailer;
- a heating device should be available for transportation in areas with extreme cold weather;
- equipment with a top air delivery system should have a fabric air chute or metal ceiling duct in good condition.

4.13 Produce requiring refrigeration should be thoroughly pre-cooled, if necessary, prior to loading into transportation equipment.

Produce temperatures should be taken with an appropriate thermometer and recorded on the bill of lading for future reference. The load compartment in the equipment also should be pre-cooled to the recommended transport or storage temperature for the produce. It is advisable that the loading area should be enclosed and if available, the loading dock doorway area should be equipped with doorway air seals.

4.14 Proper loading practices are critical to maintaining temperature and relative humidity, protecting the produce from impact and vibration forces in transit, and preventing insects from entering the load.

Special care must be taken when shipping mixed loads. The produce must be compatible.

4.15 Basic loading methods include:

- bulk loading, by machine or hand, of unpackaged commodities;
- hand loading individual shipping containers, with or without pallets;
- unit loading of palletized or slipsheet loads of containers with pallet jacks or forklifts.

4.16 Inadequate provisions for air circulation will ruin a load, even in well designed transportation equipment.

When possible, shipping containers should be kept off shallow floors and away from flat sidewalls by using pallets, racks, and dunnage.

Adequate head space between the upper row of cartons and the top of the container should be allowed; this shall be done by taping or gluing the upper row of cartons or by using appropriately designed packages for this purpose.

Room for air circulation must be provided under, around and through the load to protect the produce from:

- heat gain from the outside air during hot weather;
- heat generated by the produce through respiration;
- accumulation of ethylene from ripening of the produce;
- heat loss to the outside air during extreme cold weather;
- chilling injury or freezing injury during operation of the refrigeration unit.

4.17 Shippers using refrigerated transport equipment should follow the carrier's recommendations on loading of the equipment's load compartment to avoid chilling injury or freezing injury to the produce.

Discharge air shall be colder than the set-point temperature if the refrigeration system operates on return air temperature sensing.

4.18 Loads should be secured with one or more of the following materials to prevent the effects of vibrations and impact damage in transport and handling:

- aluminum or wood load locks;
 - paperboard or fibreboard honeycomb fillers;
- wood blocking and nailing strips;
- inflatable kraft paper air bags;
 - cargo nets and straps;
 - wood load gates constructed of 25 mm x 100 mm (1 x 4 in) material.

4.19 If available all loads should have a small air temperature recorder placed between packages in the area where the warmest temperatures occur.

Recorder companies recommend placement on top of the load, near a side wall, one-third of the way in from the rear doors, away from any direct discharge of refrigerated air. Rail cars should have two or three recorders. In loads with top-ice or humidity above 95%, the recorders should be waterproof or enclosed in a plastic bag.

2.19.1 Shippers and receivers must follow the temperature recorder companies instructions on documenting the load, starting the recorder, reading the results, and returning it for calibration and certification if necessary. These steps are essential for settling claims over temperature management during transportation.

4.20 Similar sized shipping containers should be loaded together in mixed loads for increased stability.

Heavier shipping containers of produce should be loaded first, distributed evenly across the floor of the trailer or container. Lighter shipping containers can then be placed against or on top of the heavier produce. Load lock and secure stacks of different sized shipping containers. To facilitate inspection of mixed loads at ports of entry, a representative sample of each commodity should be available near the door. This can minimize the unloading of cargo for examination.

4.21 Never load fruit, vegetables, or other food products with cargoes that provide any risk of contamination through transfer of odour or toxic chemical residues.

The longer the transit time, the higher the risks in transporting mixed loads of agricultural produce. Therefore it is essential that guidelines be followed as much as possible to maintain quality in distant markets.

4.22 Modified atmospheres of reduced oxygen and elevated carbon dioxide and nitrogen are provided to trailers and containers after loading is completed.

The trailers and containers must be equipped with channels at the doorway for a plastic film curtain and gas ports for the application of the treatment.

4.23 The refrigeration unit, walls, ceiling, floor, and doors must adequately seal the inside of the cargo area from outside air.

Otherwise the modified atmosphere will quickly dissipate. Warning labels must be applied to the equipment to warn that the atmosphere is not life supporting and that the cargo area must be properly ventilated before personnel enter to unload the cargo.

5. Packaging to maintain produce quality during transportation and marketing

5.1 Packaging must withstand:

- rough handling during loading and unloading;
- compression from the overhead weight of other containers;
- impact and vibration during transportation;
- high humidity during precooling, transit, and storage.

5.2 Packaging materials are chosen on the basis of needs of the produce, packing method, precooling method, strength, cost, availability, buyer specifications, and freight rates.

Importers, buyers, and packaging manufacturers provide valuable recommendations. Materials used include:

- paperboard or fibreboard bins, boxes (glued, stapled, interlocking), lugs, trays, flats, dividers or partitions, and slipsheets;
- wood bins, crates (wirebound, nailed), baskets, trays, lugs, pallets;
- paper bags, sleeves, wraps, liners, pads, excelsior, and labels

plastic bins, boxes, trays, bags (mesh, solid), containers, sleeves, film wraps, liners, dividers, and slipsheets;

- foam boxes, trays, lugs, sleeves, liners, dividers, and pads.

5.3 Bins, boxes, crates, trays, lugs, baskets, and bags are considered shipping containers.

Baskets, however, are difficult to handle in mixed loads of rectangular boxes. Bags provide limited produce protection.

The fibreboard type box is a widely used container. Styles include for example:

- one-piece slotted box with glued, stapled, or self-locking flaps;
- two-piece half slotted box with a cover;
- two-piece half slotted box with a full telescoping cover, providing strong walls and corners;
- three-piece Bliss-style box featuring stapled or glued ends providing strong corners;
- one-piece box with full telescoping cover;
- two-piece, die-cut style box with full telescoping cover;
- one-piece box with wire or fibreboard tabs or hardboard end inserts and plastic end caps, providing stacking strength and alignment.

5.3.1 Fibreboard boxes for produce which are packed wet or with ice must be wax-impregnated or coated with water resistant material.

The compression strength of untreated fibreboard can be reduced more than one half in conditions of 90% relative humidity. In addition to maintaining box strength, wax helps to reduce the loss of moisture from the produce to the fibreboard. All glued boxes should be made with a water resistant adhesive.

5.3.2 The majority of fibreboard boxes and wood crates are designed to be stacked top to bottom. Compression strength and produce protection are sacrificed when boxes or crates are stacked on their ends or sides. Misaligned boxes can lose up to 50% of their top to bottom compression strength.

5.4 Various materials are added to shipping containers to provide additional strength and produce protection.

Dividers or partitions and double or triple thickness sides and ends in fibreboard boxes provide additional compression strength and reduce produce damage.

5.4.1 Pads, wraps, and sleeves and excelsior also reduce bruising. Pads also are used to provide moisture as with asparagus; provide chemical treatment to reduce decay as with sulphur dioxide pads for grapes; and absorb ethylene as with potassium permanganate pads in boxes of bananas and flowers.

5.4.2 Plastic film liners or bags are used to retain moisture. Perforated plastic is used for most produce to allow exchange of gases and avoid excessive humidity. Solid plastic is used to seal the produce and provide for modified atmosphere by reducing the amount of oxygen available for respiration and ripening. For example, this is done for bananas, strawberries, tomatoes and citrus fruits.

5.5 Packing methods include:

- **field packing** - produce is placed in fibreboard boxes, plastic crates or wood crates during harvesting. Some produce is wrapped. The filled containers are then taken to a precooling facility to have the field heat removed where possible;
- **shed packing** - produce is processed or packed indoors or under cover at a central location. The produce is brought from the field to the packing shed in bulk in field crates, bins, or trucks. If available, the produce should be pre-cooled either before or after they are placed in shipping containers according to the nature of the produce;
- **repacking** - produce is taken out of one container, regraded, and placed in another. This is often done to make smaller containers for the retailer or consumer packages.

5.5.1 Types of packs include:

volume fill

- produce is placed by hand or machine into the container until the desired capacity, weight, or count is reached;
- **tray or cell pack** - produce is placed in moulded trays or cells which provide separation and reduced bruising;

- **place pack** - produce is carefully placed in the container. This provides reduced bruising and a pleasing appearance;
- **consumer pack or prepack** - relatively small amounts of produce are packaged, weighted, and labelled for retail sale;
- **film or shrink wrap** - each fruit or vegetable is individually wrapped and sealed in film to reduce moisture loss and decay. The film shall be treated with authorized fungicides or other chemicals;
- **modified atmosphere** - individual consumer packs, shipping containers, or pallet loads of containers are sealed with plastic film or bags. The oxygen level is reduced and the carbon dioxide level is increased. This reduces produce respiration and slows the ripening process.

5.6 Shipping containers must be sized and filled correctly.

Containers which are very wide and weight more than 23 kg (50 lb), for example, encourage rougher handling, produce damage, and container failure. Overfilling causes produce bruising and excessive bulging of the sides of the container, which leads to decreased compression strength and container failure. Under-filling also causes produce damage. The produce is bruised as it moves around inside the shipping container during transport and handling.

5.6.1 Due to large number of different container sizes in use, box standards are desirable.

Standardized containers:

- utilize, with other containers, the maximum surface of the pallet with no overhang and little underhang;
- provide unit loads and stable mixed pallet loads;
- reduce transportation and marketing costs.

5.7 A large number of shippers have switched from handling individual shipping containers to unit loads on pallets.

Most distribution centres are set up to store palletized loads in three tier racks.

5.7.1 Unit loads provide for:

- reduced handling of individual shipping containers;
- less damage to the containers and the produce inside;
- faster loading and unloading of transportation equipment;
- more efficient distribution centre operations.

5.7.2 Unit loads shall include, for example, some of the following features:

- standard wood pallets or slipsheets such as; 1200 x 1000 mm (48 x 40 in), 800 x 1000 mm, 800 x 1200 mm, 1000 x 1200 mm;
- fibreboard, plastic or wire vertical interlocking tabs between boxes;
- boxes with holes for air circulation, which align when the boxes are stacked squarely on top of one another, corner to corner;
- glue between boxes to resist horizontal slipping;
- plastic netting around the pallet load of boxes;

- fibreboard, plastic, or metal cornerboards;
- plastic or metal strapping around the cornerboards and boxes.

5.8 Wood pallets must be strong enough to allow storage under load.

Provisions for forklift and pallet jack handling are necessary. The design of the bottom of the pallet should not block air circulation.

5.8.1 Pallets must have an adequate number of top deck boards to support fibreboard boxes. Otherwise the boxes shall collapse between deck boards from the overhead weight of the other containers, crush the produce, and cause the entire load to lean or fall off the pallet. A sheet of fibreboard with holes for air circulation can be used to distribute air across the pallet.

5.8.2 Boxes must not overhang the edges of the pallets. Overhang can reduce the strength of fibreboard boxes by one-third. This condition also can lead to collapse of the entire load, crushing of the produce, and make loading, unloading, and storage in racks difficult. On the other hand, boxes which utilize less than 90% of the pallet surface and do not align with the pallet edge can shift in transit.

5.8.3 Pallet loads of shipping containers which are not strapped or netted should have at least the top three layers of containers cross-stacked to provide stability. Some shippers use film wrap, tape, or glue on the top layers in addition to cross-stacking. The containers must be strong enough to be cross-stacked without collapsing. Film wrap should not be used on shipping containers of produce that need ventilation.

5.9 Slipsheets are used by some shippers because they cost less than pallets.

They also eliminate the cost of transporting and returning pallets. A special forklift is needed to transfer slipsheet loads to and from the pallets at the shipper's and receiver's distribution centre. If a receiver does not have the proper handling equipment, the packages are unloaded by hand onto pallets for placement in storage. Shipping containers on slipsheets are cross-stacked, film wrapped, or otherwise unitized with cornerboards and strapping.

5.9.1 Slipsheets made of fibreboard or plastic must be strong enough to be clamped and pulled onto the forklift tines or plate for lifting while fully loaded. Fibreboard slipsheets should be wax impregnated when used in wet conditions. Slipsheets used in transportation equipment should have holes for air circulation under the load. The use of slipsheets in refrigerated transportation equipment with shallow floor channels is not recommended due to the need for adequate air circulation under the load.

6. Precooling practices

6.1 If available, the removal of field heat by the process of precooling to a recommended storage temperature and relative humidity is suggested to maintain the quality of fruits, and vegetables. The quality of most produce will rapidly deteriorate if field heat is not removed before loading into transportation equipment.

6.2 Refrigerated transportation equipment is designed to maintain temperature and should not be used to remove field heat from produce packed in shipping containers. The refrigeration units also are not capable of raising or controlling the relative humidity.

6.3 Precooling extends produce life by reducing:

- field heat;
- the rate of respiration and heat generated by the produce;
- the rate of ripening;
- the loss of moisture (shrivelling and wilting);
- the production of ethylene (ripening gas generated by the produce);
- the spread of decay.

6.4 The success of precooling is dependent on:

- time between harvest and precooling;
- type of shipping container if produce is packed beforehand;
- initial produce temperature;
- velocity or amount of cold air, water, or ice provided;
- final produce temperature;
- sanitation of the precooling air or water to reduce decay organisms.
- maintenance of the recommended temperature after precooling.

6.5 Precooling, where it is used, should occur as soon as possible after harvest. For most produce, harvesting should be done in early morning hours to minimize field heat and the refrigeration load on precooling equipment. Harvested produce should be protected from the sun with covering until they are placed in the precooling facility.

6.6 Many products are field or shed packed and then precooled. Wirebound wood or nailed crates or wax impregnated fibreboard boxes are used for packed produce that are precooled with water or ice after packing. Precooling of produce packed in shipping containers and stacked in unitized pallet loads is especially important as air circulation around and through the packaging shall be limited during transportation and storage.

6.7 The choice of precooling method depends on the nature, value, and quality of the produce as well as the cost of labour, equipment, and materials.

Precooling methods include:

- **room cooling** - stacking containers of produce in a refrigerated room. Some produce is misted or sprayed with water during room cooling;
- **forced air cooling or wet pressure cooling** - drawing air through stacks of containers of produce in a refrigerated room. For some produce, water is added to the air;
- **hydrocooling** - flushing produce in bulk tanks, bins, or shipping containers with a large quantity of ice water;
- **vacuum cooling** - removing heat from produce packed in shipping containers by drawing a vacuum in a chamber;
- **hydrovacuum cooling** - adding moisture to produce packed in shipping containers before or during the vacuum process, to speed the removal of heat;
- **package-icing** - injecting slush or crushed ice into each shipping container of produce. Some operations use bulk containers.

6.8 Since most produce is sensitive to chilling injury, care must be taken not to precool or store the produce below the recommended temperature. Often the visible effects of chilling injury are delayed until the produce is offered for retail sale. These effects include failure to ripen properly, pitting, decay, watery breakdown, and discoloration in fruits and vegetables.

6.9 All produce is sensitive to decay. Precooling equipment and water should be sanitized continuously, for example, with a hypochlorite solution to eliminate decay producing organisms. Care also must be taken not to allow produce to warm up after precooling. Condensation on cool produce surfaces at higher air temperatures also spreads decay.

6.10 The method of transportation, condition of the transport equipment, loading method, and transit and storage practices affect the success of precooling. If the recommended temperature and relative humidity are not maintained after precooling, produce quality will deteriorate.

DEAS FOR PUBLIC REVIEW COMMENTS ONLY